



Pisten Bully 400 Specifications		
Dimensions		
Width without tracks	2,500 mm	98,4"
over combined tracks	4,206 mm	165.6"
over steel tracks	4,206 mm	165.6"
over AlpineFlexTiller	5,500 mm	216.5"
Over foldable side flaps (optional)	6,400 mm	252"
Height above winch ready for operation	3,280 mm	129.1"
Height when driver's cabin tilted	3,250 mm	128.0"
Height above everything	2,830 mm	111.4"
Length with All-Way-Blade and	9.010 mm	354.7"
Ground clearance	350 mm	13.8"
Load area	2,120 x 1,920 mm (4.1 m ²) 83.5" x 75.6" (4.9yd ²)	
Weight		
Tare weight with combined tracks	7,340 kg	16,182 lbs
Tare weight with steel tracks	8,020 kg	17,681 lbs
Gross weight limit including attachments	11,800 kg	26,015 lbs
Payload on platform without winch	1,500 kg	3,300lbs
Performance Data		
Speed, continuously variable	0–23 km/h	0-14 mph
Specific ground pressure with combined	0.052 kg/cm ²	0.74 psi
Specific ground pressure with steel tracks	0.057 kg/cm ²	0.81 psi
∅ Ground coverage with AlpineFlexTiller	93,000 m ² /h	23 acres
max. Ground coverage with	126,000 m ² /h	31,1 acres
Engine		
Type	Cummins QSL 9	
Cylinders	6	
Displacement	8.9 l / 8,900 cm ³	
Power output (ECE)	272 kW (370 hp)	
Max. torque	1,519 Nm at 1,500 rpm	
Fuel consumption from	from 19 l/h	
Fuel tank capacity	260 l	
Exhaust emission standard	EUROMOT III A / EPA TIER 3	
Brakes		
Using hydromatic transmission, with no		
Two multidisk-holding brakes		
Electrics		
Voltage	24 volts	
Alternator	28 volts / 140 amps	
Batteries	2 x 12 volts / 135 Ah V3 SHD	
Cold start rating	900 A EN (50342)	
Attachments		
Front	All-Way-Blade, Front Snow-blower,	
Rear	AlpineFlexTiller, ParkFlexTiller, flexible	